



LED-Strip VARDaFlex 90 AC, IP65 230V, 9W/m, 940, 50m

Article nr.: 74938

für die Innen- und Außenanwendung, IP65 UV beständig · alle 250 mm / 14 LEDs teilbar · Anzahl der LEDs: 2800 · LED Abstand: 17,85 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 800 lm · Betriebsspannung: 230V AC · Leistung pro Meter: 9 W · Lebensdauer L70B50: >= 35.000 h · Energieeffizienzklasse: F · LxBxH in mm: 50.000 x 17 x 13,5 · Leichte lötfreie Montage durch Steckverbindungen. · Maximale Länge pro Anschluss: 50 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 50 Meter-Rolle, bereits mit Einspeisungsverbinder · und einer Endkappe · nicht dimmbar

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094749389
Housing colour	Weiss
Length	50000.00 mm
Width	17.00 mm
Height	13.50 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	40000.00 lm
Lightoutput per LED	14.29 lm
Lamp	Inklusive LED





LED-Strip VARDaFlex 90 AC, IP65 230V, 9W/m, 940, 50m

Article nr.: 74938

TECHNICAL DATA

IP rating	65
Power	450 W
Psb	0,00 W
Current mA	1956 mA
Voltage	230 V
Amount of LED	2800
Material	Kunststoff
Temperature range	-20 - 40
LED per meter	56
Dimension of segments	250.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	35.000 h
Lifetime L90B10	10.000 h





**LED-Strip VARDaFlex 90 AC, IP65 230V,
9W/m, 940, 50m**
Article nr.: 74938

TECHNICAL DRAWING

