



VARDAflex Energy - 5M-Rolle


**Flex.LEDStrip, 24V, 4, 4W/m., Innen,
3000K CRI80**

Article nr.: 79465

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · · alle 100 mm / 9 LEDs teilbar ·
Anzahl der LEDs: 450 · LED Abstand: 11,11 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro
Meter: 758 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 4,4 W · Lebensdauer L70B50: >=
54.000 h · Energieeffizienzklasse: B · LxBxH in mm: 5.000 x 10 x 1,4 · · Maximale Länge pro Anschluss:
5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm
Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094794655
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.40 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	3790.00 lm
Lightoutput per LED	8.42 lm
Lamp	Inklusive LED






VARDAflex Energy - 5M-Rolle
Flex.LEDStrip, 24V, 4, 4W/m., Innen,
3000K CRI80

Article nr.: 79465

TECHNICAL DATA

IP rating	20
Power	22 W
Psb	0,00 W
Current mA	916 mA
Voltage	24 V
Amount of LED	450
Temperature range	-20 - 45
LED per meter	90
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_B
CRI	≥ 80
Lifetime L70B50	54.000 h
Lifetime L90B10	39.000 h





VARDAflex Energy - 5M-Rolle

**Flex.LEDStrip, 24V, 4, 4W/m., Innen,
3000K CRI80**

Article nr.: 79465

TECHNICAL DRAWING

