




VARDAflex IP54 - 5M-Rolle Flex.LED-Strip, 24V, 4, 8W, IP54, 3000K

Article nr.: 79485

flexibler LED Strip mit Silikon überzogen · und selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP54 · UV-beständig · alle 100 mm / 6 LEDs teilbar · Anzahl der LEDs: 300 · LED Abstand: 16,67 mm · Ausstrahlwinkel: 120° · CRI: > 80 · Lichtstrom pro Meter: 465 lm · Leistung pro Meter: 4,8 W · Energieeffizienzklasse: F · Lebensdauer L70B50: >= 54.000 h · LxBxH in mm: 5.000 x 8 x 2,5 · Leichte lötfreie Installation durch optionale Verbinder. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094794853
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.50 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	2325.00 lm
Lightoutput per LED	7.75 lm
Lamp	Inklusive LED






VARDAflex IP54 - 5M-Rolle Flex.LED-Strip, 24V, 4, 8W, IP54, 3000K

Article nr.: 79485

TECHNICAL DATA

IP rating	54
Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	300
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	54.000 h





**VARDAflex IP54 - 5M-Rolle Flex.LED-
Strip, 24V, 4, 8W, IP54, 3000K**
Article nr.: 79485

TECHNICAL DRAWING

