




VARDAflex 4inONE-72 - IP65 - 5M- Rolle Flex.LED Strip, 24V, IP65, RGBW 3000K, CRI80

Article nr.: 79513

mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP65 · nicht UV-beständig · alle 83,33 mm / 6 LEDs teilbar · Anzahl der LEDs: 360 · LED Abstand: 13,89 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro Meter: 890 lm · Lichtstrom 3000K pro Meter: 391 lm · Betriebsspannung: 24 V DC · Leistung pro Meter: 14,4 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 14 x 4,2 · · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung, 10 x Montageklammer aus Silikon, · 20x Schrauben, 1 x Endkappe geschlossen, 1 x Endkappe Einspeisung, 1x 300 mm Anschlussleitung · zum anlöten

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094795133
Housing colour	Weiss
Length	5000.00 mm
Width	14.00 mm
Height	4.20 mm
LED colour	RGBW 3000K
Lightoutput per fixture	4450.00 lm
Lightoutput per LED	12.36 lm
Lamp	Inklusive LED





VARDAflex 4inONE-72 - IP65 - 5M- Rolle Flex.LED Strip, 24V, IP65, RGBW 3000K, CRI80

Article nr.: 79513

TECHNICAL DATA

IP rating	65
Power	72 W
Psb	0,00 W
Current mA	3000 mA
Voltage	24 V
Amount of LED	360
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h

