



VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBUWW 2700K Article nr.: 79552

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · alle 83,33 mm / 6 LEDs teilbar ·
Anzahl der LEDs: 360 · LED Abstand: 13,89 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro
Meter: 1215 lm (weiß: 592 lm) · Betriebsspannung: 24 V DC · Leistung pro Meter: 19,2 W ·
Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 12 x 2,2 ·
Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Leichte
lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5 Meter. Für
größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094795522
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.20 mm
LED colour	RGBW 2700K
Lightoutput per fixture	6075.00 lm
Lightoutput per LED	16.88 lm
Lamp	Inklusive LED





VARDAflex 4inONE-72 - 5M-Ro. Flex. LED Leiste, Innen, RGBUWW 2700K Article nr.: 79552

TECHNICAL DATA

IP rating	20
Power	96 W
Psb	0,00 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	360
Temperature range	-20 - 45
LED per meter	72
Dimension of segments	83.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h





VARDAflex 4inONE-72 - 5M-Ro. Flex.
LED Leiste, Innen, RGBUWW 2700K
Article nr.: 79552

TECHNICAL DRAWING

