




VARDAflex Eco Plus Reach15 M-R. Flex.LEDStrip, 24V, Innen, 3000K

Article nr.: 82215-V2

mit selbstklebender Rückseite, · für die Innenanwendung, IP20 · alle 50 mm / 6 LEDs teilbar · Anzahl der LEDs: 1.800 · LED Abstand: 8,33 mm · Ausstrahlwinkel: 120° · CRI: >90 · IC Baustein on board (konstante Bestromung) · Lichtstrom pro Meter: 833 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 10 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: G · LxBxH in mm: 15.000 x 10 x 1,6 · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 15 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 15 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094812151
Housing colour	Weiss
Length	15000.00 mm
Width	10.00 mm
Height	1.60 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	12495.00 lm
Lightoutput per LED	6.94 lm
Lamp	Inklusive LED





VARDAflex Eco Plus Reach15 M-R.
Flex.LEDStrip, 24V, Innen, 3000K
Article nr.: 82215-V2

TECHNICAL DATA

IP rating	20
Power	150 W
Psb	0,00 W
Current mA	6300 mA
Voltage	24 V
Amount of LED	1800
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h





VARDAflex Eco Plus Reach15 M-R.
Flex.LEDStrip, 24V, Innen, 3000K
Article nr.: 82215-V2

TECHNICAL DRAWING

