




VARDAflex Eco CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 4000K

Article nr.: 82418

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 100 mm / 7 LEDs teilbar · Anzahl der LEDs: 350 · LED Abstand: 14,28 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 445 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 4,8 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000 x 8 x 2 · · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 10 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094824185
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2225.00 lm
Lightoutput per LED	6.36 lm
Lamp	Inklusive LED





VARDAflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82418

TECHNICAL DATA

IP rating	20
Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	350
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	36.000 h
Lifetime L90B10	13.000 h





VARDAflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K
Article nr.: 82418

TECHNICAL DRAWING

