




## VARDAflex Eco IP66 - 5 M-Rolle Flex.LED Strip, 24V, IP66, 3000K

Article nr.: 82565

im Silikonschlauch mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP66 · UV-  
beständig · · alle 100 mm / 7 LEDs teilbar · Anzahl der LEDs: 350 · LED-Abstand: 14,28 mm ·  
Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 401 lm · Betriebsspannung: 24V DC ·  
Leistung pro Meter: 4,8 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: G · LxBxH in  
mm: 5.000 x 9,2 x 4,4 · · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen.  
· Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung, · 10 x Befestigungshalter, 10 x Schraube

### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | Stück              |
| BAR code                | 4012094825656      |
| Housing colour          | Weiss              |
| Length                  | 5000.00 mm         |
| Width                   | 9.20 mm            |
| Height                  | 4.40 mm            |
| LED colour              | ca. 3000K warmweiß |
| Lightoutput per fixture | 2005.00 lm         |
| Lightoutput per LED     | 5.72 lm            |
| Lamp                    | Inklusive LED      |






**VARDAflex Eco IP66 - 5 M-Rolle**  
**Flex.LED Strip, 24V, IP66, 3000K**  
Article nr.: 82565

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 66          |
| Power                   | 24 W        |
| Psb                     | 0,00 W      |
| Current mA              | 1000 mA     |
| Voltage                 | 24 V        |
| Amount of LED           | 350         |
| Temperature range       | -20 - 45    |
| LED per meter           | 70          |
| Dimension of segments   | 100.00 mm   |
| Energy efficiency class | EEK-Label_G |
| CRI                     | ≥ 90        |
| Lifetime L70B50         | 36.000 h    |
| Lifetime L90B10         | 13.000 h    |





**VARDAflex Eco IP66 - 5 M-Rolle**  
**Flex.LED Strip, 24V, IP66, 3000K**  
Article nr.: 82565

## TECHNICAL DRAWING

