




VARDAflex Eco IP66 - 5 M-Rolle Flex.LED Strip, 24V, IP66, 4000K Article nr.: 82568

im Silikonschlauch mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP66 · UV-
beständig · · alle 100 mm / 7 LEDs teilbar · Anzahl der LEDs: 350 · LED-Abstand: 14,28 mm ·
Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 410 lm · Betriebsspannung: 24V DC ·
Leistung pro Meter: 4,8 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: G · LxBxH in
mm: 5.000 x 9,2 x 4,4 · · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen.
· Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung, · 10 x Befestigungshalter, 10 x Schraube

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094825687
Housing colour	Weiss
Length	5000.00 mm
Width	9.20 mm
Height	4.40 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	2050.00 lm
Lightoutput per LED	5.86 lm
Lamp	Inklusive LED





VARDAflex Eco IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 4000K
Article nr.: 82568

TECHNICAL DATA

IP rating	66
Power	24 W
Psb	0,00 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	350
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	36.000 h
Lifetime L90B10	13.000 h





VARDAflex Eco IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 4000K
Article nr.: 82568

TECHNICAL DRAWING

