




VARDAflex Quantum COB IP65 - 5m Flex.LED Strip, 24V, IP65, 3000K, CRI80

Article nr.: 84565

im Schrumpfschlauch mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP65 · nicht UV-beständig · alle 50 mm / 24 LEDs teilbar · Anzahl der LEDs: 2400 · LED-Abstand: 2,08 mm · Ausstrahlwinkel: 180° · CRI: >80 · Lichtstrom pro Meter: 630 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 5 W · Lebensdauer L70B50: >= 54.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 8,4 x 2,3 · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung, · 10x Einspeisungs-Schrumpfschlauch, 10x Endkappen-Schrumpfschlauch

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094845654
Length	5000.00 mm
Width	8.40 mm
Height	2.30 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	3150.00 lm
Lightoutput per LED	1.32 lm
Lamp	Inklusive LED
IP rating	65






VARDAflex Quantum COB IP65 - 5m
Flex.LED Strip, 24V, IP65, 3000K, CRI80
Article nr.: 84565

TECHNICAL DATA

Power	25 W
Psb	0,00 W
Current mA	1042 mA
Voltage	24 V
Amount of LED	2400
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	480
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	54.000 h
Lifetime L90B10	20.000 h





VARDAflex Quantum COB IP65 - 5m
Flex.LED Strip, 24V, IP65, 3000K, CRI80
Article nr.: 84565

TECHNICAL DRAWING

