




VARDAflex Slim WW 10W 5M-R.
Flex.LEDStrip, 24V, Innen, 3000K CRI90
 Article nr.: 84605

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 5 cm / 7 LEDs teilbar · Anzahl der LEDs: 700 · LED Abstand: 7,14 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 927 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 10 W · Lebensdauer L70B50: >= 60.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000 x 3,5 x 1,2 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094846057
Housing colour	Weiss
Length	5000.00 mm
Width	3.50 mm
Height	1.20 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4635.00 lm
Lightoutput per LED	6.62 lm
Lamp	Inklusive LED





VARDAflex Slim WW 10W 5M-R.
Flex.LEDStrip, 24V, Innen, 3000K CRI90
Article nr.: 84605

TECHNICAL DATA

IP rating	20
Power	50 W
Psb	0,00 W
Current mA	2083 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	60.000 h
Lifetime L90B10	28.000 h





VARDAflex Slim WW 10W 5M-R.
Flex.LEDStrip, 24V, Innen, 3000K CRI90
Article nr.: 84605

TECHNICAL DRAWING

