



VARDAflex Single Select 19W 5M-R. Flex.LEDStrip, 24V, Innen, 2700-6300K Article nr.: 84859-V2

mit selbstklebender Rückseite, · für die Innenanwendung IP20 · · alle 8,33 mm / 1 LED teilbar · Anzahl der LEDs: 600 · LED Abstand: 8,33 mm · Ausstrahlwinkel: 120° · CRI: >80 · Lichtstrom pro Meter: 2129 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 19 W · Lebensdauer L70B50: >= 50.000 h · LxBxH in mm: 5.000 x 10 x 1,3 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094818597
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.30 mm
LED colour	2700-6300K tunable white
Lightoutput per fixture	10645.00 lm
Lightoutput per LED	17.74 lm
Lamp	Inklusive LED





VARDAflex Single Select 19W 5M-R.
Flex.LEDStrip, 24V, Innen, 2700-6300K
Article nr.: 84859-V2

TECHNICAL DATA

IP rating	20
Power	95 W
Psb	0,00 W
Current mA	3958 mA
Voltage	24 V
Amount of LED	600
Temperature range	-10 - 55
LED per meter	120
Dimension of segments	8.33 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	33.000 h





VARDAflex Single Select 19W 5M-R.
Flex.LEDStrip, 24V, Innen, 2700-6300K
Article nr.: 84859-V2

TECHNICAL DRAWING

