




## VARDAflex Standard IP67 Reach25 Flex.LED Strip, 24V, IP67, 3000K

Article nr.: 86550-V3

mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP67 · nicht UV-beständig · ·  
alle 100 mm / 6 LEDs teilbar · Anzahl der LEDs: 1500 · LED-Abstand: 16,67 mm · Ausstrahlwinkel:  
120° · CRI: >80 · Lichtstrom pro Meter: 385 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 3,6  
W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in mm: 25.000 x 12 x 6 · ·  
Maximale Länge pro Anschluss: 25 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 25  
Meter-Rolle mit 300 mm Anschlussleitung, · 100 x Befestigungshalter aus Silikon, 4 x  
Einspeisungskappe, · 4x Endkappe

### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | Stück              |
| BAR code                | 4012094865515      |
| Housing colour          | farblos            |
| Length                  | 25000.00 mm        |
| Width                   | 12.50 mm           |
| Height                  | 6.00 mm            |
| LED colour              | ca. 3000K warmweiß |
| Lightoutput per fixture | 10000.00 lm        |
| Lightoutput per LED     | 6.67 lm            |
| Lamp                    | Inklusive LED      |






**VARDaflex Standard IP67 Reach25  
Flex.LED Strip, 24V, IP67, 3000K**  
Article nr.: 86550-V3

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 67          |
| Power                   | 90 W        |
| Psb                     | 0,00 W      |
| Current mA              | 3750 mA     |
| Voltage                 | 24 V        |
| Amount of LED           | 1500        |
| Material                | Kunststoff  |
| Temperature range       | -25 - 45    |
| LED per meter           | 60          |
| Dimension of segments   | 50.00 mm    |
| Energy efficiency class | EEK-Label_E |
| CRI                     | ≥ 80        |
| Lifetime L70B50         | 67.000 h    |





**VARDaflex Standard IP67 Reach25  
Flex.LED Strip, 24V, IP67, 3000K**  
Article nr.: 86550-V3

## TECHNICAL DRAWING

