




VARDAflex Eco Plus IP66 - 5 M-Rolle Flex.LED Strip, 24V, IP66, 3000K

Article nr.: B82175

im Silikonschlauch mit selbstklebender Rückseite, · für die Innen- und Außenanwendung, IP66 · UV-
beständig · · alle 50 mm / 7 LEDs teilbar · Anzahl der LEDs: 700 · LED-Abstand: 7,14 mm ·
Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 980 lm · Betriebsspannung: 24V DC ·
Leistung pro Meter: 9,6 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in
mm: 5.000 x 9,5 x 4,5 · · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen ·
Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung, · 10 x Befestigungshalter, 20 x Schraube

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094221755
Housing colour	Weiss
Length	5000.00 mm
Width	9.50 mm
Height	4.50 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	4900.00 lm
Lightoutput per LED	7.00 lm
Lamp	Inklusive LED





VARDAflex Eco Plus IP66 - 5 M-Rolle Flex.LED Strip, 24V, IP66, 3000K

Article nr.: B82175

TECHNICAL DATA

IP rating	66
Power	48 W
Psb	0,0 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h





VARDAflex Eco Plus IP66 - 5 M-Rolle
Flex.LED Strip, 24V, IP66, 3000K
Article nr.: B82175

TECHNICAL DRAWING

