




VARDaflex Eco CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 3000K Box

Article nr.: B82415

mit selbstklebender Rückseite, · für die Innenanwendung · alle 100 mm / 7 LEDs teilbar · Anzahl der LEDs: 350 · LED Abstand: 14,28 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 410 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 4,8 W · Lebensdauer L70B50: >= 36.000 h · Energieeffizienzklasse: G · LxBxH in mm: 5.000 x 8 x 2 · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 10 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094224152
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	2050.00 lm
Lightoutput per LED	5.85 lm
Lamp	Inklusive LED






VARDAflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K Box
Article nr.: B82415

TECHNICAL DATA

IP rating	20
Power	24 W
Current mA	1000 mA
Voltage	24 V
Amount of LED	350
Temperature range	-20 - 45
LED per meter	70
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 90
Lifetime L70B50	36.000 h
Lifetime L90B10	13.000 h





VARDaflex Eco CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 3000K Box
Article nr.: B82415

TECHNICAL DRAWING

