



VARDAflex Eco Double CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82457

mit selbstklebender Rückseite, · für die Innenanwendung · · alle 50 mm / 8 LEDs teilbar · Anzahl der LEDs: 800 · LED Abstand: 6,25 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 2026 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 19,2 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: E · LxBxH in mm: 5.000 x 10 x 1,2 · · Achtung: LED-Strip nur mit Aluminiumprofil sowie · ausreichender Belüftung betreiben. · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094224572
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.20 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	10130.00 lm
Lightoutput per LED	12.66 lm
Lamp	Inklusive LED





VARDAflex Eco Double CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82457

TECHNICAL DATA

IP rating	20
Power	96 W
Psb	0,0 W
Current mA	4000 mA
Voltage	24 V
Amount of LED	800
Temperature range	-20 - 45
LED per meter	160
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_E
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	28.000 h





**VARDAflex Eco Double CRI90 - 5 M-
Rolle Flex.LEDStrip, 24V, Innen, 2700K
Box**

Article nr.: B82457

TECHNICAL DRAWING

