




VARDAflex Eco Plus CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 2700K Box

Article nr.: B82477

mit selbstklebender Rückseite, · für die Innenanwendung · alle 50 mm / 7 LEDs teilbar · Anzahl der LEDs: 700 · LED Abstand: 7,14 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 941 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 9,6 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000 x 8 x 1,4 · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094224770
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	1.40 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	4705.00 lm
Lightoutput per LED	6.72 lm
Lamp	Inklusive LED






VARDAflex Eco Plus CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K Box
Article nr.: B82477

TECHNICAL DATA

IP rating	20
Power	48 W
Psb	0,0 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h





VARDAflex Eco Plus CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K Box
Article nr.: B82477

TECHNICAL DRAWING

