




VARDAflex Eco Plus CRI90 - 5 M-Rolle Flex.LEDStrip, 24V, Innen, 4000K Box

Article nr.: B82478

mit selbstklebender Rückseite, · für die Innenanwendung · alle 50 mm / 7 LEDs teilbar · Anzahl der LEDs: 700 · LED Abstand: 7,14 mm · Ausstrahlwinkel: 120° · CRI: >90 · Lichtstrom pro Meter: 934 lm · Betriebsspannung: 24V DC · Leistung pro Meter: 9,6 W · Lebensdauer L70B50: >= 50.000 h · Energieeffizienzklasse: F · LxBxH in mm: 5.000 x 8 x 1,4 · Leichte lötfreie Montage durch Steckverbindungen (optional). · Maximale Länge pro Anschluss: 5 Meter. Für größere Längen neu einspeisen. · Lieferumfang: 5 Meter-Rolle mit 300 mm Anschlussleitung

TECHNICAL DATA

Unit Code	Stück
BAR code	4012094224787
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	1.40 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	4670.00 lm
Lightoutput per LED	6.67 lm
Lamp	Inklusive LED






VARDAflex Eco Plus CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K Box
Article nr.: B82478

TECHNICAL DATA

IP rating	20
Power	48 W
Psb	0,0 W
Current mA	2000 mA
Voltage	24 V
Amount of LED	700
Temperature range	-20 - 45
LED per meter	140
Dimension of segments	50.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	30.000 h





VARDAflex Eco Plus CRI90 - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 4000K Box
Article nr.: B82478

TECHNICAL DRAWING

