



Bild folgt

DALI-2 DT6 für 350-1500mA einfarbig DALI-2 Push Dimm-Aktor AC 50W

Article nr.: 80790-V2

rutech DALI-2 push dimming actuator AC · 1 address 1 channel single colour · DALI address automatically addressable from · DALI master controller (e.g. gateway) · According to DALI standard protocol IEC62386-101:2014, IEC62386-102:2014, IEC62386-207 Ed2 · suitable for commercially available DALI devices · DALI-2 or push dim function · for indoor use, IP20 · input voltage: 200-240 V AC · output current adjustable via dip switch: 350mA, 450mA, 500mA, 600mA, 650mA, 750mA, 800mA, · 900mA, 950mA, 1050mA, 1100mA, 1200mA, 1250mA, 1350mA, 1400mA, 1500mA DC · power: 2.8-50 watts depending on output current (see manual) · device type: DT6 · protection class II, CE, ROHS · protection against short circuit, overvoltage and overtemperature · dimming range: 0.1-100% PWM+CCR, flicker free · temperature range: -20°C to +45°C · LxWxH in mm: 210 x 50 x 32

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094808901
Housing colour	Blau
Length	210.00 mm
Width	50.00 mm
Height	32.00 mm
Lamp	Ohne
IP rating	20
Power	2,8-50 W
Psb	0,37 W

Equiv.
SELV



Bild folgt

DALI-2 DT6 für 350-1500mA einfarbig DALI-2 Push Dimm-Aktor AC 50W

Article nr.: 80790-V2

TECHNICAL DATA

P _{no}	0,68 W
P _{net}	0,39 W
Current mA	350-1.500 mA
Input voltage	200-240
Output voltage	8-52
Material	Kunststoff
Temperature range	-20 - 45
Suitable light source	LED



Equiv.
SELV





Bild folgt

DALI-2 DT6 für 350-1500mA einfarbig DALI-2 Push Dimm-Aktor AC 50W

Article nr.: 80790-V2

TECHNICAL DRAWING

