



## GAIL LED-Einbaustrahler 3er Set

**dimmbar Plug&play schw, rund, 300mA,  
3x6W, IP40, 3000K, CRI80-silber**

Article nr.: ALU57339WWD

for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: silver · swiveling · beam angle: 36° · power: 6 W · light colour: 3000 K · luminous flux: 718 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector and 3-way distributor for plug-and-play-operation · each downlight has 2 metres connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 120 x 45 x 28 · this product contains a light source of energy efficiency class E

### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | pcs                |
| BAR code                | 4012094573991      |
| Housing colour          | Silber             |
| Height                  | 40.00 mm           |
| Outer diameter          | 82 mm              |
| Hole size               | 68 mm              |
| Depth in ceiling        | 45.00 mm           |
| LED colour              | ca. 3000K warmweiß |
| Lightoutput per fixture | 718.00 lm          |
| Lamp                    | Inklusive LED      |





**GAIL LED-Einbaustrahler 3er Set**  
**dimmbar Plug&play schw, rund, 300mA,**  
**3x6W, IP40, 3000K, CRI80-silber**  
Article nr.: ALU57339WWD

## TECHNICAL DATA

|                   |           |
|-------------------|-----------|
| IP rating         | 40        |
| Power             | 6 W       |
| Current mA        | 300 mA    |
| Voltage           | 220-240 V |
| Lamp base         | ohne      |
| Output voltage    | 31-62     |
| Material          | Aluminium |
| Tolerance         | 5.00      |
| Efficiency        | 86.00     |
| Temperature range | -30 - 40  |
| CRI               | ≥ 80      |
| Lifetime L70B50   | 50.000 h  |

