



Quadro 3000K 25° 350mA CRI90 m.Scheibe LED Einbaustr. 8W eisengeb.o.Konv.

Article nr.: ALU53395WWOK

for indoor use, IP 20 · · housing: diecast aluminum, glass reflector, protective glass · housing color: iron brushed · 30° swivelling · beam angle: 25° · power: 8 W · light color: 3000 K · luminous flux: 733 lm · CRI: >90 · lifetime L70B50: >= 50.000 h · input: 350 mA DC · protection class III, MM · · installation depth: 40 mm · ceiling cut-out: 68 mm · outer dimensions: 82 x 82 mm · energie efficiency class: F · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094531953
Housing colour	Eisen-gebürstet
Length	82.00 mm
Width	82.00 mm
Height	31.00 mm
Hole size	68 mm
Depth in ceiling	40.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	733.00 lm






Quadro 3000K 25° 350mA CRI90 m.Scheibe LED Einbaustr. 8W eisengeb.o.Konv.

Article nr.: ALU53395WWOK

TECHNICAL DATA

Lamp	Inklusive LED
IP rating	20
Power	8 W
Current mA	350 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 90
Lifetime L70B50	50.000 h





**Quadro 3000K 25° 350mA CRI90 m.Scheibe
LED Einbaustr. 8W eisengeb.o.Konv.**

Article nr.: ALU53395WWOK

TECHNICAL DRAWING

