



## VARDAflex AC Eco 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65

Article nr.: S74928

for outdoor use, IP65 · UV resistant · can be separated every 50 cm or 27 LEDs · number of LEDs: 54 · LED pitch: 18.51 mm · beam angle: 120° · CRI: >90 · lumen per meter: 519 lm · voltage: 230V AC · power per meter: 8 W · lifetime L70B50: >= 30.000 h · energy efficiency class: G · WxH in mm: 15,5 x 6 · Easy installation with solderless connector. · Maximum length per connection: 50 meter. New connectors for greater length.

### TECHNICAL DATA

|                     |                       |
|---------------------|-----------------------|
| Unit Code           | metre                 |
| BAR code            | 4012094049281         |
| Housing colour      | Weiss                 |
| Length              | 1000.00 mm            |
| Width               | 15.50 mm              |
| Height              | 6.00 mm               |
| LED colour          | ca. 4000K neutralweiß |
| Lightoutput per LED | 9.62 lm               |
| Lamp                | Inklusive LED         |
| IP rating           | 65                    |





**VARDAflex AC Eco 4000K Flex.LED-Strip, 200-240V 50/60Hz IP65**  
Article nr.: S74928

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| Voltage                 | 220-240 V   |
| Input voltage           | 230         |
| Temperature range       | -20 - 40    |
| LED per meter           | 54          |
| Dimension of segments   | 500.00 mm   |
| Energy efficiency class | EEK-Label_G |
| CRI                     | ≥ 90        |
| Lifetime L70B50         | 30.000 h    |

