rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Quantum Plus IP65- 5 M. Rolle Flex.LEDStrip, 24V, IP65, 3000K

Article nr.: 86445

flexible LED-strip with self adhesive backside, · for indoor and outdoor use, IP65 · uv-resistant · · can be seperated every 125 mm or 8 LEDs · number of LEDs: 320 · LED pitch: 15.63 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 1688 lm · input: 24V DC · power per meter: 11.5 W · lifetime L70B50: >= 67.000 h · energy efficiency class: E · LxWxH in mm: 5.000 x 11.8 x 5.7 · · Maximum length per connection: 10 meter. New connectors for greater length. · scope of delivery: 5 meter reel with 150 mm connecting cable and plug/socket at · each end, 1x socket with 150 mm connection cable, 1x plug as end cap, · 2x silicone cap with cable feed-through, 2x silicone cap closed, · 20x silicone fixing brackets

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094864457
Length	5000.00 mm
Width	11.80 mm
Height	5.70 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	8440.00 lm
Lightoutput per LED	26.38 lm
Lamp	Inklusive LED
IP rating	65



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Quantum Plus IP65- 5 M. Rolle Flex.LEDStrip, 24V, IP65, 3000K

Article nr.: 86445

TECHNICAL DATA

Power	57,5 W
Current mA	2.395 mA
Voltage	24 V
Amount of LED	320
Material	Kunststoff
Temperature range	-20 - 45
LED per meter	64
Dimension of segments	125.00 mm
Energy ffficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	67.000 h

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Quantum Plus IP65- 5 M. Rolle Flex.LEDStrip, 24V, IP65, 3000K

Article nr.: 86445

TECHNICAL DRAWING

