rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Single UWW 21W 5M-R. Flex.LEDStrip, 24V, Innen, 2700K CRI80

Article nr.: 84853

flexible LED Strip with self adhesive backside, · for indoor use. · · can be seperated every 8.33 mm or 1 LED · number of LEDs: 600 · LED pitch: 8.33 mm · beam angle: 120° · CRI: >80 · lumen per meter: 2116 lm · voltage: 24V DC · power per meter: 21 W · lifetime L70B50: >= 60,000 h · LxWxH in mm: 5,000 x 10 x 1.5 · · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094848532
Housing colour	Weiss
Length	5000.00 mm
Width	10.00 mm
Height	1.50 mm
LED colour	ca. 2700 K ultra warmweiß
Lightoutput per fixture	10580.00 lm
Lightoutput per LED	17.63 lm
Lamp	Inklusive LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Single UWW 21W 5M-R. Flex.LEDStrip, 24V, Innen, 2700K CRI80

Article nr.: 84853

TECHNICAL DATA

IP rating	20
Power	105 W
Current mA	4.375 mA
Voltage	24 V
Amount of LED	600
Temperature range	-20 - 45
LED per meter	120
Dimension of segments	8.33 mm
CRI	≥ 80
Lifetime L70B50	60.000 h

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



VARDAflex Single UWW 21W 5M-R. Flex.LEDStrip, 24V, Innen, 2700K CRI80

Article nr.: 84853

TECHNICAL DRAWING

