



## VARDAflex Standard - 5 M-Rolle


### Flex.LEDStrip, 24V, Innen, 3000K CRI80

Article nr.: 84315

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 125 mm or 6 LEDs · Number of LEDs: 240 · LED pitch: 20.83 mm · Beam angle: 120° · CRI: >80 · Luminous flux per metre: 352 lm · Voltage: 24 V DC · Power per metre: 3.5 W · Lifetime L70B50: >= 60,000 h · Energy efficiency class: F · LxWxH in mm: 5,000 x 8 x 2.2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel, 5 in-feeder connector (profi), · 1 direct connector (profi)

#### TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Unit Code               | pcs                |
| BAR code                | 4012094843155      |
| Housing colour          | Weiss              |
| Length                  | 5000.00 mm         |
| Width                   | 8.00 mm            |
| Height                  | 2.20 mm            |
| LED colour              | ca. 3000K warmweiß |
| Lightoutput per fixture | 1760.00 lm         |
| Lightoutput per LED     | 7.33 lm            |
| Lamp                    | Inklusive LED      |





**VARDAflex Standard - 5 M-Rolle**  
**Flex.LEDStrip, 24V, Innen, 3000K CRI80**  
Article nr.: 84315

## TECHNICAL DATA

|                         |             |
|-------------------------|-------------|
| IP rating               | 20          |
| Power                   | 17,5 W      |
| Current mA              | 729 mA      |
| Voltage                 | 24 V        |
| Amount of LED           | 240         |
| Temperature range       | -20 - 45    |
| LED per meter           | 48          |
| Dimension of segments   | 125.00 mm   |
| Energy efficiency class | EEK-Label_F |
| CRI                     | ≥ 80        |
| Lifetime L70B50         | 60.000 h    |





**VARDAflex Standard - 5 M-Rolle**  
**Flex.LEDStrip, 24V, Innen, 3000K CRI80**  
Article nr.: 84315

## TECHNICAL DRAWING

