



VARDAflex Standard - 5 M-Rolle


Flex.LEDStrip, 24V, Innen, 2700K CRI80

Article nr.: 84317

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 125 mm or 6 LEDs · Number of LEDs: 240 · LED pitch: 20.83 mm · Beam angle: 120° · CRI: >80 · Luminous flux per metre: 341 lm · Voltage: 24 V DC · Power per metre: 3.5 W · Lifetime L70B50: >= 60.000 h · Energy efficiency class: F · LxWxH in mm: 5.000 x 8 x 2.2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter reel, 5 in-feeder connector (profi), · 1 direct connector (profi)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094843179
Housing colour	Weiss
Length	5000.00 mm
Width	8.00 mm
Height	2.20 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	1705.00 lm
Lightoutput per LED	7.10 lm
Lamp	Inklusive LED






VARDAflex Standard - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K CRI80
Article nr.: 84317

TECHNICAL DATA

IP rating	20
Power	17,5 W
Current mA	729 mA
Voltage	24 V
Amount of LED	240
Temperature range	-20 - 45
LED per meter	48
Dimension of segments	125.00 mm
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	60.000 h





VARDAflex Standard - 5 M-Rolle
Flex.LEDStrip, 24V, Innen, 2700K CRI80
Article nr.: 84317

TECHNICAL DRAWING

