




VARDAflex 4inONE-60 Reach10- 10M- R. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 74403-V2

flexible LED Strip with self adhesive backside, · for indoor use, IP20 · · Can be separated every 100 mm or 6 LEDs · Number of LEDs: 600 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 595 lm · luminous flux per meter: 270 lm (3000 K) · Voltage: 24V DC · Power per meter: 14.4 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 10.000 x 12 x 2 · · Easy installation with solderless connector (optional). · Maximum length per connection: 10 meter. New connectors for greater length. · Delivery contents: 10 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094724034
Housing colour	Weiss
Length	10000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGB+WW 3000K
Lightoutput per fixture	5950.00 lm
Lightoutput per LED	9.92 lm
Lamp	Inklusive LED





VARDAflex 4inONE-60 Reach10- 10M- R. Flex. LED Leiste, Innen, RGBWW 3000K

Article nr.: 74403-V2

TECHNICAL DATA

IP rating	20
Power	144 W
Psb	0,00 W
Current mA	6.000 mA
Voltage	24 V
Amount of LED	600
Temperature range	-20 - 40
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	10.000 h





**VARDAflex 4inONE-60 Reach10- 10M-
R. Flex. LED Leiste, Innen, RGBWW
3000K**

Article nr.: 74403-V2

TECHNICAL DRAWING

