



VARDAflex 4inONE-60 - 5M-Ro. Flex. LED Leiste, Innen, RGBBZ 2400K

Article nr.: 79541

flexible LED Strip with self adhesive backside, · for indoor use. · Can be separated every 10 cm or 6 LEDs · Number of LEDs: 300 · LED pitch: 16.67 mm · beam angle: 120° · CRI: >80 · luminous flux per meter: 825 lm · luminous flux 2400K per meter: 446 lm · Voltage: 24V DC · Power per meter: 19,2 W · Lifetime L70B50: >= 36.000 h · energy efficiency class: G · LxWxH in mm: 5.000 x 12 x 2 · Caution: Do not operate strip without aluminium profile · and adequate ventilation. · Easy installation with solderless connector (optional). · Maximum length per connection: 5 meter. New connectors for greater length. · Delivery contents: 5 meter roll

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094795416
Housing colour	Weiss
Length	5000.00 mm
Width	12.00 mm
Height	2.00 mm
LED colour	RGBW 2400K
Lightoutput per fixture	4125.00 lm
Lightoutput per LED	13.75 lm
Lamp	Inklusive LED





VARDAflex 4inONE-60 - 5M-Ro. Flex.
LED Leiste, Innen, RGBBZ 2400K
Article nr.: 79541

TECHNICAL DATA

IP rating	20
Power	96 W
Current mA	4.000 mA
Amount of LED	300
Input voltage	24
Temperature range	-20 - 45
LED per meter	60
Dimension of segments	100.00 mm
Energy efficiency class	EEK-Label_G
CRI	≥ 80
Lifetime L70B50	36.000 h
Lifetime L90B10	33.000 h





VARDAflex 4inONE-60 - 5M-Ro. Flex.
LED Leiste, Innen, RGBBZ 2400K
Article nr.: 79541

TECHNICAL DRAWING

