



220-240V AC, Phasenanschn. LED- Netzgerät 24V 40-75, 6W IP20 Dimmb.

Article nr.: 85480-V2

rutech dimmable LED power supply, constant voltage · for indoor use, IP20 · with screw connection and strain relief · CE, REACH, RoHS, MM, SELV · protection against short circuit, over current, over voltage and over temperature · cable cross-section connection terminals: 0.5 - 1.5 sq mm · housing: plastic · input voltage: 220-240 V AC · power: 40-75.6 W · output current: 3.15 A · output voltage: 24 V DC · LxWxH in mm: 204 x 53.5 x 30 · temperature range: -20 to +40°C · dimmable on primary side via TRIAC · depending on the electronics of the phase dimmer, the dimming range may be limited in the upper and/or lower dimming range (threshold values can be taken from the dimming electronics · used).

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094084800
Housing colour	Blau
Length	204.00 mm
Width	53.50 mm
Height	30.00 mm
Lamp	without
IP rating	20
Power	40-75,6 W
Psb	0,00 W





**220-240V AC, Phasenanschn. LED-
Netzgerät 24V 40-75, 6W IP20 Dimmb.**
Article nr.: 85480-V2

TECHNICAL DATA

Pno	
Current mA	3150 mA
Input voltage	220-240
Output voltage	24
Material	Kunststoff
Tolerance	5.00
Temperature range	-20 - 40
Suitable light source	LED





**220-240V AC, Phasenanschn. LED-
Netzgerät 24V 40-75, 6W IP20 Dimmb.**
Article nr.: 85480-V2

TECHNICAL DRAWING

