rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



220-240V AC, Phasenanschnitt LED

Netzgerät 24V 70-199, 2W IP67 dimmbar

Article nr.: 85483

rutec dimmable LED power supply, constant voltage · for indoor and outdoor use, IP67 · CE, REACH, RoHS, MM, SELV, active PFC · protection class I · protection against short circuit, overload, overtemperature and overvoltage · primary and secondary sided 1 input and output line approx. 300 mm · housing: aluminum · input voltage: 220-240V AC · Power: 70-199.2 watt · output current: 2.92-8.3 A · output voltage: 24 Volt · LxWxH in mm: 250 x 80.3 x 33.5 · temperature range: -30 to +50°C · dimmable on primary side via TRIAC dimmer · depending on the electronics of the phase dimmer, the dimming range may be limited in the · upper and/or lower dimming range (threshold values can be taken from the dimming electronics · used).

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094854830
Housing colour	Aluminium
Length	250.00 mm
Width	80.30 mm
Height	33.50 mm
Lamp	without
IP rating	67
Power	70-199,2 W
Psb	0,00 W

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



220-240V AC, Phasenanschnitt LED

Netzgerät 24V 70-199, 2W IP67 dimmbar

Article nr.: 85483

TECHNICAL DATA

Pno	<0,5 W
Current mA	2917-8300 mA
Input voltage	220-240
Output voltage	24
Material	Aluminium
Tollerance	5.00
Temperature range	-30 - 50
Suitable light source	LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



220-240V AC, Phasenanschnitt LED

Netzgerät 24V 70-199, 2W IP67 dimmbar

Article nr.: 85483

TECHNICAL DRAWING

