



220-240V AC, Phasenanschnitt LED

Netzgerät 24V 70-199, 2W IP67 dimmbar

Article nr.: 85483

rutech dimmable LED power supply, constant voltage · for indoor and outdoor use, IP67 · CE, REACH, RoHS, MM, SELV, active PFC · protection class I · protection against short circuit, overload, overtemperature and overvoltage · primary and secondary sided 1 input and output line approx. 300 mm · housing: aluminum · input voltage: 220-240V AC · Power: 70-199.2 watt · output current: 2.92-8.3 A · output voltage: 24 Volt · LxWxH in mm: 250 x 80.3 x 33.5 · temperature range: -30 to +50°C · dimmable on primary side via TRIAC dimmer · dimming range: 3-100% (depending on the dimmer used)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094854830
Housing colour	Aluminium
Length	250.00 mm
Width	80.30 mm
Height	33.50 mm
Lamp	Ohne
IP rating	67
Power	70-199,2 W
Psb	0,00 W





220-240V AC, Phasenanschnitt LED

Netzgerät 24V 70-199, 2W IP67
dimmbar

Article nr.: 85483

TECHNICAL DATA

Pno	0,48 W
Current mA	2.917-8.300 mA
Input voltage	220-240
Output voltage	24
Material	Aluminium
Tolerance	5.00
Temperature range	-30 - 50
Suitable light source	LED





220-240V AC, Phasenanschnitt LED

**Netzgerät 24V 70-199, 2W IP67
dimmbar**

Article nr.: 85483

TECHNICAL DRAWING

