



220-240V AC, SKII,

dimmb.Phasenabschnitt LED Konverter

200mA 6W-8, 4W 30-42V

Article nr.: 87375

LED Konverter, Konstantstrom-dimmbar · für die Innenanwendung, IP20 · mit Schraubanschluss und Zugentlastung · CE, REACH, RoHS, SELV · Schutz gegen Kurzschluss, Übertemperatur und Überlast · Leitungsquerschnitt Primär: 0,75 - 1,5 qmm · Leitungsquerschnitt Sekundär: 0,5 - 1,5 qmm · Gehäuse: Kunststoff · Eingangsspannung: 220-240 V AC · Leistung: 6 - 8,4 Watt · Ausgangsstrom: 200 mA · LxBxH in mm: 85 x 41 x 22 · Temperaturbereich: -20 bis +50°C · Primärseitig dimmbar Phasenabschnitt · LED converter, constant current-dimmable · for indoor use, IP20 · with screw connection and strain relief · CE, REACH, RoHS, SELV · Protection against short circuit, over temperature and overload · Primary cable cross-section: 0.75-1.5 sqmm · Secondary cable cross-section: 0.5-1.5 sqmm · Housing: plastic · Input voltage: 220-240 V AC · Power: 6-8.4 watts · Output current: 200 mA · LxWxH in mm: 85 x 41 x 22 · Temperature range: -20 to +50°C · Primary side dimmable with trailing edge dimmer

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094873756
Housing colour	Weiss
Length	85.00 mm
Width	41.00 mm
Height	22.00 mm
Lamp	without
IP rating	20
Power	6-8,4 W
Pno	



Equiv.
SELV





220-240V AC, SKII,

dimmb.Phasenabschnitt LED Konverter

200mA 6W-8, 4W 30-42V

Article nr.: 87375

TECHNICAL DATA

Current mA	200 mA
Input voltage	220-240
Output voltage	30-42
Material	Kunststoff
Temperature range	-20 - 50
Suitable light source	LED



Equiv.
SELV





**220-240V AC, SKII,
dimmb.Phasenabschnitt LED Konverter
200mA 6W-8, 4W 30-42V**
Article nr.: 87375

TECHNICAL DRAWING

