



## Glas - schwarz AC-DALI Touchpanel 4 ZONEN RGBW

Article nr.: 80530

DALI touch panel, 4 zones RGBW, including power supply for 230 V AC connection · for indoor use · Material: plastic, glass · IP20 · Protection class II, CE, RoHS · Voltage: 100 – 230 V AC, 50 Hz · Standby power: 1,5 W · Transmission power: max. 4 W · Signal: DALI · Device Type: DT6 · Maximum cable cross-section at terminal: 1.5 sq mm · DALI start address manually adjustable via 2 potentiometer · per zone: address management of 4 addresses possible · in acc. w. DALI standard protocol IEC 62386-102, IEC 62386-207 · suitable for standard DALI devices · Dimmer range 0.1 – 100 % · Control up to 4 zones independently · highly sensitive touch colour wheel · quick, precise colour control · Selection of 10 different preprogrammed colour gradients · dimming and switching of single and mixed colors · per zone: 4 memory functions for colour scene or - sequence · several DALI touch panels per DALI bus line possible

### TECHNICAL DATA

|                  |               |
|------------------|---------------|
| Unit Code        | pcs           |
| BAR code         | 4012094805306 |
| Housing colour   | Schwarz       |
| Length           | 86.00 mm      |
| Width            | 86.00 mm      |
| Height           | 42.00 mm      |
| Hole size        | 55 mm         |
| Depth in ceiling | 50.00 mm      |
| Lamp             | Ohne          |
| IP rating        | 20            |





## Glas - schwarz AC-DALI Touchpanel 4 ZONEN RGBW

Article nr.: 80530

### TECHNICAL DATA

|                   |          |
|-------------------|----------|
| Power             | 2 W      |
| Input voltage     | 100-240  |
| Material          | Glas     |
| Temperature range | -20 - 50 |

