rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



schwenkbar 1, 4401 X5CrNiMo 316 Tulka Edelstahl V4A mit Clipverschl. ws

Article nr.: R5558-1

Item No. R5558-1 · Adjustable, Without Snap- · Ring for 50 mm Light Bulb · · Indoor and Outdoor Use Also Usable for Installation In Concrete Ceilings and · Other Thermally Difficult Mounting Locations. As Well As for Use In Moist Rooms · and Suitable for Sea Air Areas · V4A-Stainless Steel-Downlight · Light Bulb Replacement: Adjustable Panel Removable (Clip Fastener) · Excluding: Light Bulb · without low-voltage socket item no.: 55004 (SKIII) · without high-voltage socket + strain relief item no.: 54995 (SKII)

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094555812
Housing colour	Weiss
Outer diameter	82 mm
Hole size	68 mm
Lamp	without
IP rating	20
Power	1-50 W
Lamp base	ohne
Amount of LED	1

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



schwenkbar 1, 4401 X5CrNiMo 316 Tulka Edelstahl V4A mit Clipverschl. ws

Article nr.: R5558-1

TECHNICAL DATA

Material	Edelstahl
Temperature range	-20 - 100
Suitable light source	

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



schwenkbar 1, 4401 X5CrNiMo 316 Tulka Edelstahl V4A mit Clipverschl. ws

Article nr.: R5558-1

TECHNICAL DRAWING

