rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

350mA MELIMAR LED Lichtpunkt 1x3, 2W UWW

Article nr.: LED56981UWW

for indoor use, IP 40 · · housing: solid aluminum · housing color: aluminum · not swivelling · beam angle: 40° · power: 3.2 W · light color: 3000 K · luminous flux: 345 lm · CRI: >80 · lifetime L70B50: >= 54.000 h · input: 350 mA DC · protection class III · · installation depth: 33 mm · ceiling cut-out: 34 mm · outer diameter: 40 mm · energie efficiency class: E · not included LED converter

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094539812
Housing colour	Aluminium
Height	26.00 mm
Outer diameter	40 mm
Hole size	34 mm
Depth in ceiling	33.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	345.00 lm
Lamp	including LED

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

350mA MELIMAR LED Lichtpunkt 1x3, 2W UWW

Article nr.: LED56981UWW

TECHNICAL DATA

IP rating	40
Power	3,2 W
Psb	0,00 W
Current mA	350 mA
Material	Aluminium
Temperature range	-20 - 40
Energy ffficiency class	EEK-Label_E
CRI	≥ 80
Lifetime L70B50	54.000 h
Lifetime L90B10	46.000 h
Suitable light source	

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE

350mA MELIMAR LED Lichtpunkt 1x3, 2W UWW

Article nr.: LED56981UWW

TECHNICAL DRAWING