



Zubehör CYRA+ CC21W150-500CG2-1, m. Kabel u. Stecker

Article nr.: 21960

Konstantstrom Konverter, DC fähig, On/Off · für die Innenanwendung, IP20 · mit Federdruckklemmen, Zugentlastung, Durchverdrahtungstauglich · Schutzklasse II, CE, REACH, RoHS, MM, SELV · Schutz gegen Überlast, Kurzschluss und Leerlauf · Gehäuse: Kunststoff · Eingangsspannung: 200-240 V AC 50/60 Hz, 170-276 V DC · Ausgangsstrom: 150-500 mA per Dipschalter einstellbar in 50 mA Schritten · Leistung: 2,3-22,5 W je nach Ausgangsstrom (siehe Anleitung) · Ausgangsspannung: 15-45 V DC je nach Ausgangsstrom (siehe Anleitung) · Temperaturbereich: -20 bis +45 °C · LxBxH in mm: 192 x 59 x 23 · Constant current converter, DC capable, On/Off · for indoor use, IP20 · with spring pressure terminals, strain relief, suitable for through-wiring · Protection class II, CE, REACH, RoHS, MM, SELV · Protection against overload, short circuit and open circuit · Housing: Plastic · Input voltage: 200-240 V AC 50/60 Hz, 170-276 V DC · Output current: 150-500 mA adjustable in 50 mA steps via dip switch · Power: 2.3-22.5 W depending on output current (see instructions) · Output voltage: 15-45 V DC depending on output current (see instructions) · Temperature range: -20 to +45 °C · LxWxH in mm: 192 x 59 x 23

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094219608
Housing colour	Weiss
Length	192.00 mm
Width	59.00 mm
Height	23.00 mm
Lamp	without
IP rating	20
Power	2,3-22,5 W
Pno	





Zubehör CYRA+ CC21W150-500CG2-1, m. Kabel u. Stecker

Article nr.: 21960

TECHNICAL DATA

Current mA	150-500 mA
Input voltage	220-240
Output voltage	15-45
Material	Kunststoff
Tolerance	5.00
Temperature range	-20 - 45
Suitable light source	LED





**Zubehör CYRA+ CC21W150-500CG2-1,
m. Kabel u. Stecker**
Article nr.: 21960

TECHNICAL DRAWING

