



Zubehör CYRA+ CC30W350-700CG2-1, m. Kabel u. Stecker

Article nr.: 21961

Konstantstrom Konverter, DC fähig, On/Off · für die Innenanwendung, IP20 · mit Federdruckklemmen, Zugentlastung, Durchverdrahtungstauglich · Schutzklasse II, CE, REACH, RoHS, MM, SELV · Schutz gegen Überlast, Kurzschluss und Leerlauf · Gehäuse: Kunststoff · Eingangsspannung: 200-240 V AC 50/60 Hz, 170-276 V DC · Ausgangsstrom: 350-700 mA per Dipschalter einstellbar in 50 mA Schritten · Leistung: 9,4-31,5 W je nach Ausgangsstrom (siehe Anleitung) · Ausgangsspannung: 27-45 V DC · Temperaturbereich: -20 bis +45°C · LxBxH in mm: 192 x 59 x 23 · Constant current converter, DC capable, On/Off · for indoor use, IP20 · with spring pressure terminals, strain relief, suitable for through-wiring · Protection class II, CE, REACH, RoHS, MM, SELV · Protection against overload, short circuit and open circuit · Housing: Plastic · Input voltage: 200-240 V AC 50/60 Hz, 170-276 V DC · Output current: 350-700 mA adjustable in 50 mA steps via dip switch · Power: 9.4-31.5 W depending on output current (see instructions) · Output voltage: 27-45 V DC · Temperature range: -20 to +45°C · LxWxH in mm: 192 x 59 x 23

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094219615
Housing colour	Weiss
Length	192.00 mm
Width	59.00 mm
Height	23.00 mm
Lamp	without
IP rating	20
Power	9,4-31,5 W
Pno	






Zubehör CYRA+ CC30W350-700CG2-1, m. Kabel u. Stecker

Article nr.: 21961

TECHNICAL DATA

Current mA	350-700 mA
Input voltage	220-240
Output voltage	27-45
Material	Kunststoff
Tolerance	5.00
Temperature range	-20 - 45
Suitable light source	LED





**Zubehör CYRA+ CC30W350-700CG2-1,
m. Kabel u. Stecker**
Article nr.: 21961

TECHNICAL DRAWING

