**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# Zubehör CYRA+ DALI-2 LC27MINI-DA-150-700, mit Stecker

Article nr.: 21970

DALI-2 push dimming actuator AC · 1 address 1 channel single colour · DALI address automatically addressable from · DALI master controller (e.g. gateway) · According to DALI standard protocol IEC62386-101:2014, IEC62386-102:2014, IEC62386-207 Ed2 · suitable for commercially available DALI devices · DALI-2 or push dim function · for indoor use, IP20 · input voltage: 220-240 V AC 50/60 Hz, 198-254 V DC · Output current (150-700 mA) adjustable via dip-switch in 50 mA steps · power: 1.4-26.3 watts depending on ouput current (see manual) · device type: DT6 · protection class II, CE, ROHS · protection against short circuit, overload and overtemperature · dimming range: 1-100 % amplitude dimming, flicker free · dimming curve: linear · temperature range: -20 °C to +45 °C · LxWxH in mm: 225 x 56 x 30

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094219707 |
| Housing colour | Weiss |
| Length | 225.00 mm |
| Width | 56.00 mm |
| Height | 30.00 mm |
| Lamp | without |
| IP rating | 20 |
| Power | 1,4-26,3 W |
| Pno | <0,5 W |



**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# Zubehör CYRA+ DALI-2 LC27MINI-DA-150-700, mit Stecker

Article nr.: 21970

## TECHNICAL DATA

| | |
|---|---|
| Current mA | 150-700 mA |
| Input voltage | 220-240 |
| Output voltage | 9-52 |
| Material | Kunststoff |
| Tollerance | 5.00 |
| Temperature range | -20 - 45 |
| Suitable light source | LED |

rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# Zubehör CYRA+ DALI-2 LC27MINI-DA-150-700, mit Stecker

Article nr.: 21970

## TECHNICAL DRAWING

