rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



Notlichtbetriebsgerät CYRA+ EC25-3031050LI, DC10-50V, 3W, 220-240V AC

Article nr.: 21980

The emergency lighting control unit is a decentralised power supply for emergency · and safety. In the event of a failure in the mains power supply, the battery integrated into the · unit automatically takes over the power supply and ensures that escape and evacuation routes remain · illuminated. · · input voltage: 220-240 V AC, 50/60 Hz · emergency output voltage: 10-50 V DC, max. 55 V (SELV) · emergency power: 3 W (constant power) · emergency operating time: >3 h · battery type: LiFePO4 6.4V 2.2Ah · capacity: 2200 mAh · protection against short circuit, overload and open circuit · protection rating: IP20 · protection class II, CE, SELV, REACH, RoHS · operating temperature: 0°C to +50°C · primary and secondary sides with plug-in terminals for 0.5 - 1.5 sqmm · housing: plastic · LxWxH in mm: 212 x 73 x 28

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094219806
Housing colour	Weiss
Length	212.00 mm
Width	73.00 mm
Height	28.00 mm
Lamp	without
IP rating	20
Power	3 W
Psb	0,00 W



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke

TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



Notlichtbetriebsgerät CYRA+ EC25-3031050LI, DC10-50V, 3W, 220-240V AC

Article nr.: 21980

TECHNICAL DATA

Pno	<2 W
Current mA	2200 mA
Input voltage	220-240
Output voltage	10-50
Material	Kunststoff
Temperature range	-5 - 50
Suitable light source	LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



Notlichtbetriebsgerät CYRA+ EC25-3031050LI, DC10-50V, 3W, 220-240V AC

Article nr.: 21980

TECHNICAL DRAWING

