



**CYRA+ M Refit LED-Downlight, On/Off,
Refl., fa. starr, rd, 230V, 18/24W, IP20,
4000K, CRI80, RAL9016, asy**

Article nr.: C+M-1-4-NW-80-AS-11

Downlight for indoor use, IP20 · Front ring of galvanised sheet steel, powder-coated · COB module carrier and lens interchangeable · Faceted trumpet reflector made of ultra-pure aluminium, highly specular · Housing colour: RAL9016 · High-quality PMMA optic for precise light control and very good glare control · Homogeneous symmetrical illumination, UGR<19 · Beam angle: asymmetrical (wall washing) · Power: 18 or 24 W · Light colour: 4000 K · Luminous flux: 2580 or 3540 lm · CRI: >80 · Lifespan L70B50: >= 60,000 h · Lifespan L80B10: >= 50,000 h · Input voltage: 220-240 V AC, 50/60 Hz · Protection class II · Installation depth: 85 mm · Ceiling cut-out: 200-225 mm · Outer diameter: 237 mm · Tool-free installation in the ceiling with tension springs that adapt to the ceiling thickness · (1 - 30 mm) · Installation in concrete pots possible · On/Off control gear with luminaire cable pre-assembled for easy installation · Suitable for through-wiring · Can be used in central battery emergency lighting systems in accordance with EN61347-2-13 Annex J · This product contains a light source of energy efficiency class C

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094200002
Housing colour	Weiss
Height	85.00 mm
Outer diameter	237 mm
Hole size	225 mm
Depth in ceiling	85.00 mm
LED colour	ca. 4000K neutralweiß
Lightoutput per fixture	3540.00 lm
Lamp	including LED





**CYRA+ M Refit LED-Downlight, On/Off,
Refl., fa. starr, rd, 230V, 18/24W, IP20,
4000K, CRI80, RAL9016, asy**
Article nr.: C+M-1-4-NW-80-AS-11

TECHNICAL DATA

IP rating	20
Power	18-24 W
Psb	0,00 W
Current mA	500-700 mA
Voltage	220-240 V
Lamp base	sonstige
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 80
Lifetime L70B50	60.000 h
Lifetime L90B10	42.000 h
Suitable light source	





**CYRA+ M Refit LED-Downlight, On/Off,
Refl., fa. starr, rd, 230V, 18/24W, IP20,
4000K, CRI80, RAL9016, asy**
Article nr.: C+M-1-4-NW-80-AS-11

TECHNICAL DRAWING

