



**CYRA M Eco Refit LED-Downlights,
On/Off, DA200-225mm CYRA M, 230V,
7/9/14W, IP20, 3000K, CRI80, RAL9010**
Article nr.: 21041WW

Downlight for indoor use, IP20 · Front ring of galvanised sheet steel, powder-coated · Module support of galvanised sheet steel · Trumpet reflector of ultra-pure aluminium, powder-coated matt white · Housing colour: RAL9010 · High-quality PMMA optic for precise light control and very good glare control · Homogeneous symmetrical illumination, UGR<19 · Beam angle: 60° · Power: 7, 9 or 14 W · Light colour: 3000 K · Luminous flux: 1000, 1300 or 2000 lm · CRI: >80 · Lifespan L70B50: >= 60,000 h · Lifespan L80B10: >= 50,000 h · Input voltage: 220-240 V AC, 50/60 Hz · Protection class II · Installation depth: 80 mm · Ceiling cut-out: 200-225 mm · Outer diameter: 237 mm · Tool-free installation in the ceiling with tension springs that adapt to the ceiling thickness · (1 - 30 mm) · Installation in concrete pots possible · On/Off control gear with luminaire cable pre-assembled for easy installation · Suitable for through-wiring · This product contains a light source of energy efficiency class D

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094214412
Housing colour	RAL9010
Height	80.00 mm
Outer diameter	237 mm
Hole size	200 mm
Depth in ceiling	80.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	2000.00 lm
Lamp	Inklusive LED





CYRA M Eco Refit LED-Downlights,
On/Off, DA200-225mm CYRA M, 230V,
7/9/14W, IP20, 3000K, CRI80, RAL9010
Article nr.: 21041WW

TECHNICAL DATA

IP rating	20
Power	7-14 W
Psb	0,00 W
Current mA	200-400 mA
Voltage	220-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 80
Lifetime L70B50	60.000 h





CYRA M Eco Refit LED-Downlights,
On/Off, DA200-225mm CYRA M, 230V,
7/9/14W, IP20, 3000K, CRI80, RAL9010
Article nr.: 21041WW

TECHNICAL DRAWING

