**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE




# CYRA L Eco Refit LED-Downlights, On/Off, DA230-255mm CYRA L, 230V, 7/9/14W, IP20, 4000K, CRI80, RAL9010

Article nr.: 21061NW

Downlight for indoor use, IP20 · Front ring of galvanised sheet steel, powder-coated · Module support of galvanised sheet steel · Trumpet reflector of ultra-pure aluminium, powder-coated matt white · Housing colour: RAL9010 · High-quality PMMA optic for precise light control and very good glare control · Homogeneous symmetrical illumination, UGR<19 · Beam angle: 60° · Power: 7, 9 or 14 W · Light colour: 4000 K · Luminous flux: 1000, 1300 or 2000 lm · CRI: >80 · Lifespan L70B50: >= 60,000 h · Lifespan L80B10: >= 50,000 h · Input voltage: 220-240 V AC, 50/60 Hz · Protection class II · Installation depth: 80 mm · Ceiling cut-out: 230-255 mm · Outer diameter: 270 mm · Tool-free installation in the ceiling with tension springs that adapt to the ceiling thickness · (1 - 30 mm) · Installation in concrete pots possible · On/Off control gear with luminaire cable pre-assembled for easy installation · Suitable for through-wiring · This product contains a light source of energy efficiency class D · · SECONDLIFE ITEM -heavily discounted- only while stocks last!

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094212616 |
| Housing colour | RAL9010 |
| Height | 80.00 mm |
| Outer diameter | 270 mm |
| Hole size | 230 mm |
| Depth in ceiling | 80.00 mm |
| LED colour | ca. 4000K neutralweiß |
| Lightoutput per fixture | 2000.00 lm |
| Lamp | including LED |



**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE




# CYRA L Eco Refit LED-Downlights, On/Off, DA230-255mm CYRA L, 230V, 7/9/14W, IP20, 4000K, CRI80, RAL9010

Article nr.: 21061NW

## TECHNICAL DATA

| | |
|---|---|
| IP rating | 20 |
| Power | 7-14 W |
| Psb | 0,00 W |
| Current mA | 200-400 mA |
| Voltage | 220-240 V |
| Lamp base | ohne |
| Material | Aluminium |
| Temperature range | -20 - 50 |
| CRI | ≥ 80 |
| Lifetime L70B50 | 60.000 h |
| Suitable light source | |



**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE




# CYRA L Eco Refit LED-Downlights, On/Off, DA230-255mm CYRA L, 230V, 7/9/14W, IP20, 4000K, CRI80, RAL9010

Article nr.: 21061NW

## TECHNICAL DRAWING

