



2700K 15°-45° 700mA CRI80 LED Fokus Einbaustr.6, 9W eisengeb. o.Konv.

Article nr.: ALU58485UWWOK

for indoor use, IP20 · Housing: diecast aluminum · Housing colour: iron brushed · swivel · Beam angle: focusable 15 - 45° · Power: 6,9 W · Light colour: 2700 K · Light flux: 570 lm · CRI: >80 · Lifespan L70B50: >= 50.000 h · Input current: 700 mA DC · protection class III · Installation depth: 70 mm · Ceiling cut-out: 68 mm · Outer diameter: 82 mm · Energie efficiency class: F · not including LED converter · SECONDLIFE ITEM -heavily discounted- only while stocks last!

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094584850
Housing colour	Eisen-gebürstet
Height	60.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	60.00 mm
LED colour	ca. 2700K ultra warmweiß
Lightoutput per fixture	570.00 lm
Lamp	including LED





2700K 15°-45° 700mA CRI80 LED Fokus Einbaustr.6, 9W eisengeb. o.Konv.

Article nr.: ALU58485UWWOK

TECHNICAL DATA

IP rating	20
Power	6,9 W
Current mA	700 mA
Lamp base	ohne
Amount of LED	1
Material	Aluminium
Temperature range	-20 - 40
Energy efficiency class	EEK-Label_F
CRI	≥ 80
Lifetime L70B50	50.000 h
Suitable light source	





2700K 15°-45° 700mA CRI80 LED Fokus
Einbaustr.6, 9W eisengeb. o.Konv.
Article nr.: ALU58485UWWOK

TECHNICAL DRAWING

