



GAIL Einbaustrahler, dimmbar, multicolour, plug&play schwenkb, rund, 6W, IP65, 27/30/4000K, CRI90-weiß matt

Article nr.: ALU57251SWD

for indoor and outdoor use, IP65 · with switchable light colour on the converter · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: matt white · swiveling · beam angle: 40° · power: 6 W · light colour: 2700/3000/4000 K · luminous flux: 600 lm · CRI: >90 · lifespan L70B50: >= 50,000 h · input voltage range: 200-240 V AC, 50/60 Hz · protection class II · installation depth: 55 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via TRIAC dimmer · with connector for plug-and-play-operation with 400 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 99 x 38 x 28 · this product contains a light source of energy efficiency class F

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094572260
Housing colour	Weiss matt
Height	45.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	55.00 mm
LED colour	2700/3000/4000 K umschaltbar
Lightoutput per fixture	600.00 lm
Lamp	including LED





**GAIL Einbaustrahler, dimmbar,
multicolour, plug&play schwenkb, rund,
6W, IP65, 27/30/4000K, CRI90-weiß
matt**

Article nr.: ALU57251SWD

TECHNICAL DATA

IP rating	65
Power	6 W
Psb	0,00 W
Voltage	200-240 V
Lamp base	ohne
Material	Aluminium
Temperature range	-20 - 50
CRI	≥ 90
Lifetime L70B50	50.000 h
Lifetime L90B10	46.000 h
Suitable light source	





**GAIL Einbaustrahler, dimmbar,
multicolour, plug&play schwenkb, rund,
6W, IP65, 27/30/4000K, CRI90-weiß
matt**

Article nr.: ALU57251SWD

TECHNICAL DRAWING

