



GAIL LED-Einbaustrahler 1er Set DimToWarm Plug&play schwenk, rund, 300mA, 6W, IP40, 3-1900K, CRI95- schwarz matt

Article nr.: ALU57302DTW

for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: black · swiveling · beam angle: 36° · power: 6 W · light colour: 3000-1900 K Dim To Warm · luminous flux: 430 lm · CRI: >95 · lifespan L70B50: >= 50,000 h · input voltage range: 200-264 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector for plug-and-play-operation with 500 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 109 x 40 x 22 · this product contains a light source of energy efficiency class G · MOQ COLORED BOX 2000 PCS · COLORS CAN BE MIXED · ALU5730XDTW

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094573021
Housing colour	schwarz matt
Height	40.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	3000-1900K Dim to Warm
Lightoutput per fixture	430.00 lm
Lamp	including LED





GAIL LED-Einbaustrahler1er Set
DimToWarm Plug&play schwenk, rund,
300mA, 6W, IP40, 3-1900K, CRI95-
schwarz matt

Article nr.: ALU57302DTW

TECHNICAL DATA

IP rating	40
Power	6 W
Current mA	300 mA
Voltage	220-240 V
Amount of LED	1
Input voltage	200-264
Output voltage	15-30
Material	Aluminium
Efficiency	82.00
Temperature range	-30 - 85
CRI	≥ 95
Lifetime L70B50	50.000 h
Lifetime L90B10	46.000 h
Suitable light source	





GAIL LED-Einbaustrahler 1er Set
DimToWarm Plug&play schwenk, rund,
300mA, 6W, IP40, 3-1900K, CRI95-
schwarz matt

Article nr.: ALU57302DTW

TECHNICAL DRAWING

