



## GAIL LED-Einbaustrahler 1er Set

### DimToWarm Plug&play schwenk, rund, 300mA, 6W, IP40, 3-1900K, CRI95- silber

Article nr.: ALU57309DTW

for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: silver · swiveling · beam angle: 36° · power: 6 W · light colour: 3000-1900 K Dim To Warm · luminous flux: 430 lm · CRI: >95 · lifespan L70B50: >= 50,000 h · input voltage range: 200-264 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector for plug-and-play-operation with 500 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 109 x 40 x 22 · this product contains a light source of energy efficiency class G

#### TECHNICAL DATA

|                         |                        |
|-------------------------|------------------------|
| Unit Code               | pcs                    |
| BAR code                | 4012094573090          |
| Housing colour          | Silber                 |
| Height                  | 40.00 mm               |
| Outer diameter          | 82 mm                  |
| Hole size               | 68 mm                  |
| Depth in ceiling        | 45.00 mm               |
| LED colour              | 3000-1900K Dim to Warm |
| Lightoutput per fixture | 430.00 lm              |
| Lamp                    | including LED          |





## GAIL LED-Einbaustrahler1er Set

### DimToWarm Plug&play schwenk, rund, 300mA, 6W, IP40, 3-1900K, CRI95- silber

Article nr.: ALU57309DTW

#### TECHNICAL DATA

|                       |           |
|-----------------------|-----------|
| IP rating             | 40        |
| Power                 | 6 W       |
| Current mA            | 300 mA    |
| Voltage               | 220-240 V |
| Amount of LED         | 1         |
| Input voltage         | 200-264   |
| Output voltage        | 15-30     |
| Material              | Aluminium |
| Efficiency            | 82.00     |
| Temperature range     | -30 - 85  |
| CRI                   | ≥ 95      |
| Lifetime L70B50       | 50.000 h  |
| Lifetime L90B10       | 46.000 h  |
| Suitable light source |           |





**GAIL LED-Einbaustrahler1er Set**  
**DimToWarm Plug&play schwenk, rund,**  
**300mA, 6W, IP40, 3-1900K, CRI95-**  
**silber**

Article nr.: ALU57309DTW

## TECHNICAL DRAWING

