



GAIL LED-Einbaustrahler 1er Set

DimToWarm Plug&play schwenk, rund, 300mA, 6W, IP40, 3-1900K, CRI95- silber

Article nr.: ALU57309DTW

for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: silver · swiveling · beam angle: 36° · power: 6 W · light colour: 3000-1900 K Dim To Warm · luminous flux: 430 lm · CRI: >95 · lifespan L70B50: >= 50,000 h · input voltage range: 200-264 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector for plug-and-play-operation with 500 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 109 x 40 x 22 · this product contains a light source of energy efficiency class G

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094573090
Housing colour	Silber
Height	40.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	3000-1900K Dim to Warm
Lightoutput per fixture	430.00 lm
Lamp	Inklusive LED





GAIL LED-Einbaustrahler1er Set
DimToWarm Plug&play schwenk, rund,
300mA, 6W, IP40, 3-1900K, CRI95-
silber

Article nr.: ALU57309DTW

TECHNICAL DATA

IP rating	40
Power	6 W
Current mA	300 mA
Voltage	220-240 V
Amount of LED	1
Input voltage	200-264
Output voltage	15-30
Material	Aluminium
Efficiency	82.00
Temperature range	-30 - 85
CRI	≥ 95
Lifetime L70B50	50.000 h

