



GAIL LED-Einbaustrahler 1er Set on-off
plug&play schwenkb., rund, 300mA,
6W, IP40, 3000K, CRI80-silber
 Article nr.: ALU57309WW


for indoor use, IP40 · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: silver · swiveling · beam angle: 36° · power: 6 W · light colour: 3000 K · luminous flux: 718 lm · CRI: >80 · lifespan L70B50: ≥ 50,000 h · input voltage range: 200-264 V AC, 50/60 Hz · protection class II · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including switchable constant current converter · with connector for plug-and-play-operation with 500 mm connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 95 x 35 x 24 · this product contains a light source of energy efficiency class E

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094573298
Housing colour	Silber
Height	40.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	718.00 lm
Lamp	including LED



Equiv.
SELV





GAIL LED-Einbaustrahler 1er Set on-off
plug&play schwenkb., rund, 300mA,
6W, IP40, 3000K, CRI80-silber
 Article nr.: ALU57309WW

TECHNICAL DATA

IP rating	40
Power	6 W
Current mA	300 mA
Voltage	220-240 V
Lamp base	ohne
Input voltage	180-264
Output voltage	14-24
Material	Aluminium
Tolerance	5.00
Efficiency	76.00
Temperature range	-30 - 40
CRI	≥ 80
Lifetime L70B50	50.000 h
Lifetime L90B10	46.000 h
Suitable light source	





GAIL LED-Einbaustrahler 1er Set on-off
plug&play schwenkb., rund, 300mA,
6W, IP40, 3000K, CRI80-silber
Article nr.: ALU57309WW

TECHNICAL DRAWING

