rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



GAIL LED-Einbaustrahler 3er Set dimmbar Plug&play schw., rund, 300mA, 3x6W, IP40, 3000K, CRI80- weiß matt

Article nr.: ALU57331WWD

for indoor use, IP40 · · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: white · swiveling · beam angle: 36° · power: 6 W · light colour: 3000 K · luminous flux: 718 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector and 3-way distributor for plug-and-play-operation · each downlight has 2 metres connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 120 x 45 x 28 · this product contains a light source of energy efficiency class E

TECHNICAL DATA

Unit Code	pcs
BAR code	4012094573915
Housing colour	Weiss matt
Height	40.00 mm
Outer diameter	82 mm
Hole size	68 mm
Depth in ceiling	45.00 mm
LED colour	ca. 3000K warmweiß
Lightoutput per fixture	718.00 lm
Lamp	Inklusive LED



rutec Licht GmbH & Co. KG | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



GAIL LED-Einbaustrahler 3er Set dimmbar Plug&play schw., rund, 300mA, 3x6W, IP40, 3000K, CRI80- weiß matt

Article nr.: ALU57331WWD

TECHNICAL DATA

IP rating	40
Power	6 W
Current mA	300 mA
Voltage	220-240 V
Lamp base	ohne
Output voltage	31-62
Material	Aluminium
Tollerance	5.00
Efficiency	86.00
Temperature range	-30 - 40
CRI	≥ 80
Lifetime L70B50	50.000 h

