**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# GAIL LED-Einbaustrahler 3er Set dimmbar Plug&play schw., rund, 300mA, 3x6W, IP40, 3000K, CRI80- schwarz matt

Article nr.: ALU57332WWD

for indoor use, IP40 · · housing: diecast aluminium, PC reflector, transparent plastic cover · housing colour: black · swiveling · beam angle: 36° · power: 6 W · light colour: 3000 K · luminous flux: 718 lm · CRI: >80 · lifespan L70B50: >= 50,000 h · input voltage range: 220-240 V AC, 50/60 Hz · protection class II · · installation depth: 45 mm · ceiling cut out: 68 mm · outer diameter: 82 mm · including constant current converter dimmable via phase cut dimmer · with connector and 3-way distributor for plug-and-play-operation · each downlight has 2 metres connection cable · tool-free replacement of the lamp · LxWxH constant current converter in mm: 120 x 45 x 28 · this product contains a light source of energy efficiency class E

## TECHNICAL DATA

| | |
|---|---|
| Unit Code | pcs |
| BAR code | 4012094573922 |
| Housing colour | schwarz matt |
| Height | 40.00 mm |
| Outer diameter | 82 mm |
| Hole size | 68 mm |
| Depth in ceiling | 45.00 mm |
| LED colour | ca. 3000K warmweiß |
| Lightoutput per fixture | 718.00 lm |
| Lamp | Inklusive LED |



**rutec Licht GmbH & Co. KG** | Carl-Zeiss-Str. 15 | 28857 Syke
TEL +49 (0) 42 42 95 65 - 0 | FAX +49 (0) 42 42 95 65 - 25 | E-MAIL INFO@RUTEC.DE | WWW.RUTEC.DE



# GAIL LED-Einbaustrahler 3er Set dimmbar Plug&play schw., rund, 300mA, 3x6W, IP40, 3000K, CRI80- schwarz matt

Article nr.: ALU57332WWD

## TECHNICAL DATA

| | |
|---|---|
| IP rating | 40 |
| Power | 6 W |
| Current mA | 300 mA |
| Voltage | 220-240 V |
| Lamp base | ohne |
| Output voltage | 31-62 |
| Material | Aluminium |
| Tollerance | 5.00 |
| Efficiency | 86.00 |
| Temperature range | -30 - 40 |
| CRI | ≥ 80 |
| Lifetime L70B50 | 50.000 h |